

## And main Technical Parameters:

Characteristics: The double air chamber lifejacket is designed and produced according to SoLAs 74/96, LSa stipulation and it is MSC. 218 (82)amendment and MSC. 81(70)lifesaving equipment standards. It has two separate air chambers which respectively connect with auto and manual inflation device. If one air chamber loses buoyancy, the inflation of another air chamber can be achieved by manually pulling the toggle, which double ensures the immersion into water it can be inflated within five seconds. It is a device for passengers on board and also suitable for offshore operation. this lifejacket is approved by China Classification Society(ccs)and Register of Fishing Vessel of the People's Republic of China

Main technical parameters:

1)Weight: ≤1.5kg; 2)Freeboard≥120mm; 3)Inflation time:≤5s, 4)Float duration: ≥24h;

5)Buoyancy lossafter 24h: ≤5%;

6) Light intensity of position light: 0. 75cd, light duration: 8h;

7)Ambient temperature for use: -30C+65C;

8) Validity: 3 years

型号 Model No	规格 Specification	充气方式 Inflation method	浮力 Buoyancy	CO <sub>2</sub> 气体重量 CO <sub>2</sub> weight
ZHCQY(B)ZS	双气室 Double air chamber	自动+手动 Automatic+manual	≥150Nx2	33gx2
		自动+手动 Automatic+manual	≥120Nx2	24gx2

## **COMPANY ADVANTAGE**













## **CORPORATE CERTIFICATE**



## Ningbo Zhenhua Electrical Equipment Co.Ltd.

Address:No.111 yingang rd., xizhou, xiangshan, zhejiang province, china Post No.: 315700 Phone:+86-136 0678 3177
Tel:+86-574-87898900 Tel:+86-574-87896971
Fax:+86-574-87896981 E-mail:nb9@zhen-hua.com
Company Website:www.lifesavingseries.com